LX - 1500 SUPER

SWING OVER CARRIAGE	MM	400
MAX. TURNING DIA.	MM	630
MAX. TURNING LENGTH	MM	1525
TRAVEL (X / Z)	MM	325 / 1525
RAPID FEED (X / Z)	M/MIN	20
SPINDLE SPEED RANGE	RPM	50 - 1500
SPINDLE POWER (FANUC)	kW	15 / 18 (P)
SPINDLE BORE	MM	110
SPINDLE NOSE		A2 - 11
WEIGHT (APPROX)	KG	-





LX - 2000

SWING OVER CARRIAGE	MM	400
MAX. TURNING DIA.	MM	630
MAX. TURNING LENGTH	MM	2025
TRAVEL (X / Z)	MM	325 / 2025
RAPID FEED (X / Z)	M/MIN	20
SPINDLE SPEED RANGE	RPM	50 - 2500
SPINDLE POWER (FANUC)	kW	11 / 15 (P)
SPINDLE BORE	MM	90
SPINDLE NOSE		A2 - 8
WEIGHT (APPROX)	KG	-

LX - 2000 SUPER

SWING OVER CARRIAGE.	MM	400
MAX. TURNING DIA.	MM	630
MAX. TURNING LENGTH	MM	2025
TRAVEL (X / Z)	MM	325 / 2025
RAPID FEED (X / Z)	M/MIN	20
SPINDLE SPEED RANGE	RPM	50 - 1500
SPINDLE POWER (FANUC)	kW	15 / 18 (P)
SPINDLE BORE	MM	110
SPINDLE NOSE		A2 - 11
WEIGHT (APPROX)	KG	-

