MONO A - 5



SWING OVER CARRIAGE	MM	320
MAX. TURNING DIA.	MM	320
MAX. TURNING LENGTH	MM	325
TRAVEL (X / Z)	MM	170 / 325
RAPID FEED (X / Z)	M/MIN	30 / 30
CHUCK SIZE	MM	165x3
SPINDLE POWER (FANUC)	kW	5.5 / 7.5
SPINDLE BORE	MM	54
SPINDLE NOSE		A2 - 5
WEIGHT (APPROX)	KG	-

MONO A - 6

SWING OVER CARRIAGE	MM	320
MAX. TURNING DIA.	MM	320
MAX. TURNING LENGTH	MM	325
TRAVEL (X / Z)	MM	170 / 325
RAPID FEED (X / Z)	M/MIN	30 / 30
CHUCK SIZE	MM	200x3
SPINDLE POWER (FANUC)	kW	7.5 / 11
SPINDLE BORE	MM	63
SPINDLE NOSE		A2 - 6
WEIGHT (APPROX)	KG	-



MONO - 200



SWING OVER CARRIAGE	MM	350
MAX. TURNING DIA.	MM	350
MAX. TURNING LENGTH	MM	550
TRAVEL (X / Z)	MM	185 / 550
RAPID FEED (X / Z)	M/MIN	24
CHUCK SIZE	MM	200x3
SPINDLE POWER (FANUC)	kW	9 / 12 (P)
SPINDLE BORE	MM	63
SPINDLE NOSE		A2 - 6
WEIGHT (APPROX)	KG	3900

MONO - 200 XL

SWING OVER CARRIAGE	MM	350
MAX. TURNING DIA.	MM	350
MAX. TURNING LENGTH	MM	700
TRAVEL (X / Z)	MM	185 / 700
RAPID FEED (X / Z)	M/MIN	24
CHUCK SIZE	MM	200x3
SPINDLE POWER (FANUC)	kW	9 / 12 (P)
SPINDLE BORE	MM	63
SPINDLE NOSE		A2 - 6
WEIGHT (APPROX)	KG	4350





MONO - 250

SWING OVER CARRIAGE	MM	350
MAX. TURNING DIA.	MM	350
MAX. TURNING LENGTH	MM	550
TRAVEL (X / Z)	MM	185 / 550
RAPID FEED (X / Z)	M/MIN	24
CHUCK SIZE	MM	250x3
SPINDLE POWER (FANUC)	kW	11 / 15
SPINDLE BORE	MM	63
SPINDLE NOSE		A2 - 6
WEIGHT (APPROX)	KG	4050

MONO – 250 XL



SWING OVER CARRIAGE	MM	350
MAX. TURNING DIA.	MM	350
MAX. TURNING LENGTH	MM	700
TRAVEL (X / Z)	MM	185 / 700
RAPID FEED (X / Z)	M/MIN	24
CHUCK SIZE	MM	250x3
SPINDLE POWER (FANUC)	kW	11 / 15
SPINDLE BORE	MM	63
SPINDLE NOSE		A2 – 6
WEIGHT (APPROX)	KG	4450

MONO – 300 SUPER

SWING OVER CARRIAGE	MM	500
MAX. TURNING DIA.	MM	500
MAX. TURNING LENGTH	MM	550
TRAVEL (X / Z)	MM	260 / 550
RAPID FEED (X / Z)	M/MIN	24
CHUCK SIZE	MM	305x3
SPINDLE POWER (FANUC)	kW	11 / 15 (P)
SPINDLE BORE	MM	90
SPINDLE NOSE		A2 – 8
WEIGHT (APPROX)	KG	5000



MONO – 300 SUPER XL



SWING OVER CARRIAGE	MM	500
MAX. TURNING DIA.	MM	500
MAX. TURNING LENGTH	MM	800
TRAVEL (X / Z)	MM	260 / 800
RAPID FEED (X / Z)	M/MIN	24
CHUCK SIZE	MM	305x3
SPINDLE POWER (FANUC)	kW	11 / 15 (P)
SPINDLE BORE	MM	90
SPINDLE NOSE		A2 – 8
WEIGHT (APPROX)	KG	5150

MONO - 400



SWING OVER CARRIAGE	MM	500
MAX. TURNING DIA.	MM	500
MAX. TURNING LENGTH	MM	525
TRAVEL (X / Z)	MM	260 / 525
RAPID FEED (X / Z)	M/MIN	24
CHUCK SIZE	MM	380x3
SPINDLE POWER (FANUC)	kW	15 / 18.5 (P)
SPINDLE BORE	MM	110
SPINDLE NOSE		A2 - 11
WEIGHT (APPROX)	KG	5500

MONO - 400 XL

SWING OVER CARRIAGE	MM	500
MAX. TURNING DIA.	MM	500
MAX. TURNING LENGTH	MM	800
TRAVEL (X / Z)	MM	260 / 800
RAPID FEED (X / Z)	M/MIN	24
CHUCK SIZE	MM	380x3
SPINDLE POWER (FANUC)	kW	15 / 18.5 (P)
SPINDLE BORE	MM	110
SPINDLE NOSE		A2 - 11
WEIGHT (APPROX)	KG	-

