MONO - 200



SWING OVER CARRIAGE	MM	350
MAX. TURNING DIA.	MM	350
MAX. TURNING LENGTH	MM	550
TRAVEL (X / Z)	MM	185 / 550
RAPID FEED (X / Z)	M/MIN	24
CHUCK SIZE	MM	200x3
SPINDLE POWER (FANUC)	kW	9 / 12 (P)
SPINDLE BORE	MM	63
SPINDLE NOSE		A2 - 6
WEIGHT (APPROX)	KG	3900

MONO - 200 XL

SWING OVER CARRIAGE	MM	350
MAX. TURNING DIA.	MM	350
MAX. TURNING LENGTH	MM	700
TRAVEL (X / Z)	MM	185 / 700
RAPID FEED (X / Z)	M/MIN	24
CHUCK SIZE	MM	200x3
SPINDLE POWER (FANUC)	kW	9 / 12 (P)
SPINDLE BORE	MM	63
SPINDLE NOSE		A2 - 6
WEIGHT (APPROX)	KG	4350





MONO - 250

SWING OVER CARRIAGE	MM	350
MAX. TURNING DIA.	MM	350
MAX. TURNING LENGTH	MM	550
TRAVEL (X / Z)	MM	185 / 550
RAPID FEED (X / Z)	M/MIN	24
CHUCK SIZE	MM	250x3
SPINDLE POWER (FANUC)	kW	11 / 15
SPINDLE BORE	MM	63
SPINDLE NOSE		A2 - 6
WEIGHT (APPROX)	KG	4050