MONO – 250 XL



SWING OVER CARRIAGE	MM	350
MAX. TURNING DIA.	MM	350
MAX. TURNING LENGTH	MM	700
TRAVEL (X / Z)	MM	185 / 700
RAPID FEED (X / Z)	M/MIN	24
CHUCK SIZE	MM	250x3
SPINDLE POWER (FANUC)	kW	11 / 15
SPINDLE BORE	MM	63
SPINDLE NOSE		A2 – 6
WEIGHT (APPROX)	KG	4450

MONO – 300 SUPER

SWING OVER CARRIAGE	MM	500
MAX. TURNING DIA.	MM	500
MAX. TURNING LENGTH	MM	550
TRAVEL (X / Z)	MM	260 / 550
RAPID FEED (X / Z)	M/MIN	24
CHUCK SIZE	MM	305x3
SPINDLE POWER (FANUC)	kW	11 / 15 (P)
SPINDLE BORE	MM	90
SPINDLE NOSE		A2 – 8
WEIGHT (APPROX)	KG	5000



MONO – 300 SUPER XL



SWING OVER CARRIAGE	MM	500
MAX. TURNING DIA.	MM	500
MAX. TURNING LENGTH	MM	800
TRAVEL (X / Z)	MM	260 / 800
RAPID FEED (X / Z)	M/MIN	24
CHUCK SIZE	MM	305x3
SPINDLE POWER (FANUC)	kW	11 / 15 (P)
SPINDLE BORE	MM	90
SPINDLE NOSE		A2 – 8
WEIGHT (APPROX)	KG	5150