PRO – 400 V

TABLE SIZE	MM	630x300
AXIS STROKE (X / Y / Z)	MM	400 / 350 / 400
RAPID FEED RATES X/Y/Z AXIS	M/MIN	24 / 24 / 24
LOAD CAPACITY	KG	300
SPINDLE	-	BT 40
RATED POWER	KW	5.5 / 7.5
WEIGHT (APPROX)	KG	2000
DIMENSIONS (APPROX) (WXDXH)	MM	1650x2618x2450





PRO – 500 V

TABLE SIZE	MM	650x400
AXIS STROKE (X / Y / Z)	MM	500 / 450 / 400
RAPID FEED RATES X/Y/Z AXIS	M/MIN	24 / 24 / 24
LOAD CAPACITY	KG	350
SPINDLE	-	BT 40
RATED POWER	KW	5.5 / 7.5
WEIGHT (APPROX)	KG	2800
DIMENSIONS (APPROX) (WXDXH)	MM	1750x2620x2520

PRO – 600 V

TABLE SIZE	MM	750x400
AXIS STROKE (X / Y / Z)	MM	600 / 450 / 500
RAPID FEED RATES X/Y/Z AXIS	M/MIN	24 / 24 / 24
LOAD CAPACITY	KG	400
SPINDLE	-	BT 40
SPINDLE POWER (FANUC)	KW	5.5 / 7.5
WEIGHT (APPROX)	KG	3100
DIMENSIONS (APPROX) (WXDXH)	MM	2120x2690x2615



PRO - 700 V

TABLE SIZE	MM	850x400
AXIS STROKE (X / Y / Z)	MM	700 / 450 / 500
RAPID FEED RATES X/Y/Z AXIS	M/MIN	24 / 24 / 24
LOAD CAPACITY	KG	400
SPINDLE	-	BT 40
RATED POWER	KW	5.5 / 7.5
WEIGHT (APPROX)	KG	3400
DIMENSIONS (APPROX) (WXDXH)	MM	2120x2690x2615





PRO - 800 V

TABLE SIZE	MM	1000x500
AXIS STROKE (X / Y / Z)	MM	800 / 500 / 500
RAPID FEED RATES X/Y/Z AXIS	M/MIN	24 / 24 / 24
LOAD CAPACITY	KG	500
SPINDLE	-	BT 40
RATED POWER	KW	7.5 / 11
WEIGHT (APPROX)	KG	4600
DIMENSIONS (APPROX) (WXDXH)	MM	2602x2842x2878