

TMC - 250

SWING OVER CARRIAGE	MM	180
MAX. TURNING DIA.	MM	180
MAX. TURNING LENGTH	MM	250
TRAVEL (X / Z)	MM	100 / 250
RAPID FEED (X / Z)	M/MIN	30
CHUCK SIZE	MM	165x3
SPINDLE POWER (FANUC)	kW	7.5 / 11
SPINDLE BORE	MM	54
SPINDLE NOSE		A2 - 5
WEIGHT (APPROX)	KG	-

TMC - 250 SUPER

SWING OVER CARRIAGE	MM	180
MAX. TURNING DIA.	MM	180
MAX. TURNING LENGTH	MM	250
TRAVEL (X / Z)	MM	100 / 250
RAPID FEED (X / Z)	M/MIN	30
CHUCK SIZE	MM	200x3
SPINDLE POWER (FANUC)	kW	7.5 / 11
SPINDLE BORE	MM	63
SPINDLE NOSE		A2 - 6
WEIGHT (APPROX)	KG	-





TMC - 300

SWING OVER CARRIAGE	MM	250
MAX. TURNING DIA.	MM	250
MAX. TURNING LENGTH	MM	320
TRAVEL (X / Z)	MM	135 / 320
RAPID FEED (X / Z)	M/MIN	30
CHUCK SIZE	MM	165x3
SPINDLE POWER (FANUC)	kW	7.5 / 11
SPINDLE BORE	MM	54
SPINDLE NOSE		A2 - 5
WEIGHT (APPROX)	KG	-



TMC - 300 SUPER

SWING OVER CARRIAGE	MM	250
MAX. TURNING DIA.	MM	250
MAX. TURNING LENGTH	MM	320
TRAVEL (X / Z)	MM	135 / 320
RAPID FEED (X / Z)	M/MIN	30
CHUCK SIZE	MM	200x3
SPINDLE POWER (FANUC)	kW	7.5 / 11
SPINDLE BORE	MM	63
SPINDLE NOSE		A2 - 6
WEIGHT (APPROX)	KG	-