

VIBRANT - 900

TABLE SIZE (CLAMPING AREA)	MM	500x1100
AXIS STROKE (X / Y / Z)	MM	900 / 550 / 550
RAPID FEED RATES X/Y/Z AXIS	M/MIN	30/30/30
LOAD CAPACITY	KG	900
SPINDLE	-	BT - 40
RATED POWER (FANUC)	KW	7.5 / 11
WEIGHT (APPROX)	KG	5040
DIMENSIONS (APPROX) (WXDXH)	MM	2677x2842x2878

VIBRANT - 1055

TABLE SIZE (CLAMPING AREA)	MM	500x1200
AXIS STROKE (X / Y / Z)	MM	1050 / 510 / 510
RAPID FEED RATES X/Y/Z AXIS	M/MIN	30/30/30
LOAD CAPACITY	KG	1000
SPINDLE	-	BT - 40 / BT - 50
RATED POWER (FANUC)	KW	11 / 15
WEIGHT (APPROX)	KG	6200
DIMENSIONS (APPROX) (WXDXH)	MM	2745x3168x3057





VIBRANT - 1066

TABLE SIZE (CLAMPING AREA)	MM	600x1120
AXIS STROKE (X / Y / Z)	MM	1020 / 610 / 610
RAPID FEED RATES X/Y/Z AXIS	M/MIN	30/30/24
LOAD CAPACITY	KG	1200
SPINDLE	-	BT - 40 / BT - 50
RATED POWER (FANUC)	KW	11 / 15
WEIGHT (APPROX)	KG	-
DIMENSIONS (APPROX) (WXDXH)	MM	2883x3325x3310 (BT-40) 2883x3325x3395 (BT-50)