

VIBRANT - 400

TABLE SIZE (CLAMPING AREA)	MM	300x600
AXIS STROKE (X / Y / Z)	MM	410 / 300 / 300
RAPID FEED RATES X/Y/Z AXIS	M/MIN	30/30/30
LOAD CAPACITY	KG	250
SPINDLE	-	BT - 40
RATED POWER (FANUC)	KW	5.5 / 7.5
WEIGHT (APPROX)	KG	3150
DIMENSIONS (APPROX) (WXDXH)	MM	1911x2618x2500

VIBRANT - 500

TABLE SIZE (CLAMPING AREA)	MM	450x650
AXIS STROKE (X / Y / Z)	MM	525 / 500 / 500
RAPID FEED RATES X/Y/Z AXIS	M/MIN	30/30/30
LOAD CAPACITY	KG	500
SPINDLE	-	BT - 40
RATED POWER (FANUC)	KW	5.5 / 7.5
WEIGHT (APPROX)	KG	4060
DIMENSIONS (APPROX) (WXDXH)	MM	2332x2845x2890





VIBRANT - 600

TABLE SIZE (CLAMPING AREA)	MM	500x800
AXIS STROKE (X / Y / Z)	MM	600 / 500 / 500
RAPID FEED RATES X/Y/Z AXIS	M/MIN	30/30/30
LOAD CAPACITY	KG	500
SPINDLE	-	BT - 40
RATED POWER (FANUC)	KW	5.5 / 7.5
WEIGHT (APPROX)	KG	4360
DIMENSIONS (APPROX) (WXDXH)	MM	2332x2845x2890