


## VIBRANT - 400

| | | |
|---|---|---|
| TABLE SIZE (CLAMPING AREA) | MM | 300x600 |
| AXIS STROKE (X / Y / Z) | MM | 410 / 300 / 300 |
| RAPID FEED RATES X/Y/Z AXIS | M/MIN | 30/30/30 |
| LOAD CAPACITY | KG | 250 |
| SPINDLE | - | BT - 40 |
| RATED POWER (FANUC) | KW | 5.5 / 7.5 |
| WEIGHT (APPROX) | KG | 3150 |
| DIMENSIONS (APPROX) (WXDXH) | MM | 1911x2618x2500 |

## VIBRANT - 500

| | | |
|---|---|---|
| TABLE SIZE (CLAMPING AREA) | MM | 450x650 |
| AXIS STROKE (X / Y / Z) | MM | 525 / 500 / 500 |
| RAPID FEED RATES X/Y/Z AXIS | M/MIN | 30/30/30 |
| LOAD CAPACITY | KG | 500 |
| SPINDLE | - | BT - 40 |
| RATED POWER (FANUC) | KW | 5.5 / 7.5 |
| WEIGHT (APPROX) | KG | 4060 |
| DIMENSIONS (APPROX) (WXDXH) | MM | 2332x2845x2890 |







## VIBRANT - 600

| | | |
|---|---|---|
| TABLE SIZE (CLAMPING AREA) | MM | 500x800 |
| AXIS STROKE (X / Y / Z) | MM | 600 / 500 / 500 |
| RAPID FEED RATES X/Y/Z AXIS | M/MIN | 30/30/30 |
| LOAD CAPACITY | KG | 500 |
| SPINDLE | - | BT - 40 |
| RATED POWER (FANUC) | KW | 5.5 / 7.5 |
| WEIGHT (APPROX) | KG | 4360 |
| DIMENSIONS (APPROX) (WXDXH) | MM | 2332x2845x2890 |