

VX - 300

SWING OVER CARRIAGE	MM	280
MAX. TURNING DIA.	MM	320
MAX. TURNING LENGTH	MM	325
TRAVEL (X / Z)	MM	170 / 325
RAPID FEED (X / Z)	M/MIN	30
CHUCK SIZE	MM	165x3
SPINDLE POWER (FANUC)	kW	5.5 / 7.5
SPINDLE BORE	MM	54
SPINDLE NOSE		A2 - 5
WEIGHT (APPROX)	KG	2900

VX - 300 SUPER

SWING OVER CARRIAGE	MM	280
MAX. TURNING DIA.	MM	320
MAX. TURNING LENGTH	MM	325
TRAVEL (X / Z)	MM	170 / 325
RAPID FEED (X / Z)	M/MIN	30
CHUCK SIZE	MM	200x3
SPINDLE POWER (FANUC)	kW	7.5 / 11
SPINDLE BORE	MM	63
SPINDLE NOSE		A2 - 6
WEIGHT (APPROX)	KG	3000





VX - 400

SWING OVER CARRIAGE	MM	280
MAX. TURNING DIA.	MM	320
MAX. TURNING LENGTH	MM	425
TRAVEL (X / Z)	MM	170 / 425
RAPID FEED (X / Z)	M/MIN	30
CHUCK SIZE	MM	200x3
SPINDLE POWER (FANUC)	kW	5.5 / 7.5
SPINDLE BORE	MM	54
SPINDLE NOSE		A2 - 5
WEIGHT (APPROX)	KG	3000



VX - 400 SUPER

SWING OVER CARRIAGE	MM	280
MAX. TURNING DIA.	MM	320
MAX. TURNING LENGTH	MM	425
TRAVEL (X / Z)	MM	170 / 425
RAPID FEED (X / Z)	M/MIN	30
CHUCK SIZE	MM	200x3
SPINDLE POWER (FANUC)	kW	7.5 / 11
SPINDLE BORE	MM	63
SPINDLE NOSE		A2 - 6
WEIGHT (APPROX)	KG	3100

VX - 550

SWING OVER CARRIAGE	MM	280
MAX. TURNING DIA.	MM	350
MAX. TURNING LENGTH	MM	550
TRAVEL (X / Z)	MM	185 / 550
RAPID FEED (X / Z)	M/MIN	30
CHUCK SIZE	MM	200x3
SPINDLE POWER (FANUC)	kW	9 / 12 (P)
SPINDLE BORE	MM	63
SPINDLE NOSE		A2 - 6
WEIGHT (APPROX)	KG	3100





VX - 550 SUPER

SWING OVER CARRIAGE	MM	280
MAX. TURNING DIA.	MM	350
MAX. TURNING LENGTH	MM	550
TRAVEL (X / Z)	MM	185 / 550
RAPID FEED (X / Z)	M/MIN	24
CHUCK SIZE	MM	250x3
SPINDLE POWER (FANUC)	kW	11 / 15
SPINDLE BORE	MM	90
SPINDLE NOSE		A2 - 8
WEIGHT (APPROX)	KG	3200



VX - 700

SWING OVER CARRIAGE	MM	280
MAX. TURNING DIA.	MM	350
MAX. TURNING LENGTH	MM	700
TRAVEL (X / Z)	MM	185 / 700
RAPID FEED (X / Z)	M/MIN	24
CHUCK SIZE	MM	200x3
SPINDLE POWER (FANUC)	kW	9 / 12 (P)
SPINDLE BORE	MM	63
SPINDLE NOSE		A2 - 6
WEIGHT (APPROX)	KG	3400

VX - 700 SUPER

SWING OVER CARRIAGE	MM	280
MAX. TURNING DIA.	MM	350
MAX. TURNING LENGTH	MM	700
TRAVEL (X / Z)	MM	185 / 700
RAPID FEED (X / Z)	M/MIN	24
CHUCK SIZE	MM	250x3
SPINDLE POWER (FANUC)	kW	11 / 15
SPINDLE BORE	MM	90
SPINDLE NOSE		A2 - 8
WEIGHT (APPROX)	KG	3500

