

VX - 300

SWING OVER CARRIAGE	MM	280
MAX. TURNING DIA.	MM	320
MAX. TURNING LENGTH	MM	325
TRAVEL (X / Z)	MM	170 / 325
RAPID FEED (X / Z)	M/MIN	30
CHUCK SIZE	MM	165x3
SPINDLE POWER (FANUC)	kW	5.5 / 7.5
SPINDLE BORE	MM	54
SPINDLE NOSE		A2 - 5
WEIGHT (APPROX)	KG	2900

VX - 300 SUPER

SWING OVER CARRIAGE	MM	280
MAX. TURNING DIA.	MM	320
MAX. TURNING LENGTH	MM	325
TRAVEL (X / Z)	MM	170 / 325
RAPID FEED (X / Z)	M/MIN	30
CHUCK SIZE	MM	200x3
SPINDLE POWER (FANUC)	kW	7.5 / 11
SPINDLE BORE	MM	63
SPINDLE NOSE		A2 - 6
WEIGHT (APPROX)	KG	3000





VX - 400

SWING OVER CARRIAGE	MM	280
MAX. TURNING DIA.	MM	320
MAX. TURNING LENGTH	MM	425
TRAVEL (X / Z)	MM	170 / 425
RAPID FEED (X / Z)	M/MIN	30
CHUCK SIZE	MM	200x3
SPINDLE POWER (FANUC)	kW	5.5 / 7.5
SPINDLE BORE	MM	54
SPINDLE NOSE		A2 - 5
WEIGHT (APPROX)	KG	3000