

VX - 400 SUPER

SWING OVER CARRIAGE	MM	280
MAX. TURNING DIA.	MM	320
MAX. TURNING LENGTH	MM	425
TRAVEL (X / Z)	MM	170 / 425
RAPID FEED (X / Z)	M/MIN	30
CHUCK SIZE	MM	200x3
SPINDLE POWER (FANUC)	kW	7.5 / 11
SPINDLE BORE	MM	63
SPINDLE NOSE		A2 - 6
WEIGHT (APPROX)	KG	3100

VX - 550

SWING OVER CARRIAGE	MM	280
MAX. TURNING DIA.	MM	350
MAX. TURNING LENGTH	MM	550
TRAVEL (X / Z)	MM	185 / 550
RAPID FEED (X / Z)	M/MIN	30
CHUCK SIZE	MM	200x3
SPINDLE POWER (FANUC)	kW	9 / 12 (P)
SPINDLE BORE	MM	63
SPINDLE NOSE		A2 - 6
WEIGHT (APPROX)	KG	3100





VX - 550 SUPER

SWING OVER CARRIAGE	MM	280
MAX. TURNING DIA.	MM	350
MAX. TURNING LENGTH	MM	550
TRAVEL (X / Z)	MM	185 / 550
RAPID FEED (X / Z)	M/MIN	24
CHUCK SIZE	MM	250x3
SPINDLE POWER (FANUC)	kW	11 / 15
SPINDLE BORE	MM	90
SPINDLE NOSE		A2 - 8
WEIGHT (APPROX)	KG	3200